



YOUR VISION

OUR CREATION

**Solid Wood Technical Information**



|                     |   |
|---------------------|---|
| <b>Product</b>      | <b>Diamond Plus Eng Hickory<br/>Rustic Stain H/S Lacq<br/>127mm 14/3mm RL</b> |
| <b>Number</b>       | <b>501900</b>   |
| <b>Construction</b> | <b>Engineered Multilayer</b>  |
| <b>Size</b>         | <b>127mm x 14mm x RL</b>  |
| <b>Finished</b>     | <b>UV Matt Lacquered</b>  |

|   |  |
|---|--|
| <b>Structure</b>                        | <b>Engineered Multi-layer</b>  |
| <b>Veneer Thickness (if applicable)</b> | <b>4mm +/-0.30mm</b>   |
| <b>Length Spec (including average)</b>  | <b>400-1200 Ave 750</b>  |
| <b>Width Tolerance</b>                  | <b>+/- 0.2mm</b>   |
| <b>Type of Finish</b>                   | <b>Gold Stained &amp; UV Matt lacquered.<br/>Handscraped textured finish</b> |
| <b>Gloss Level</b>                      | <b>10% +/-5%</b>   |
| <b>Live Knot &amp; Filler Colour</b>    | <b>Up to 30mm in size, Dark Brown Filler</b>                                 |
| <b>Dead Knot</b>                        | <b>&lt;30mm filled</b>   |
| <b>Colour Difference</b>                | <b>Colour difference between boards allowed</b>                              |
| <b>Sapwood</b>                          | <b>Stained</b>   |
| <b>Grain</b>                            | <b>All grains patterns acceptable</b>  |
| <b>Split</b>                            | <b>Not allowed</b>   |
| <b>Formaldehyde</b>                     | <b>E1</b>  |
| <b>Bowing</b>                           | <b>&lt;0.5% of the length</b>  |
| <b>Moisture Content</b>                 | <b>8-10%</b>   |
| <b>Installation Method</b>              | <b>Float or stuck down</b>   |
| <b>Suitable to use with UHF</b>         | <b>Yes, see guide</b>  |



YOUR VISION

OUR CREATION

### Solid Wood Technical Information



|                     |  |
|---------------------|--|
| <b>Product</b>      | <b>Diamond Plus Eng Oak<br/>Antique Natural Stain H/S<br/>Lacq 125mm 14/3mm RL</b> |
| <b>Number</b>       | <b>501917</b>  |
| <b>Construction</b> | <b>Engineered Multilayer</b>   |
| <b>Size</b>         | <b>125mm x 18mm x RL</b>   |
| <b>Finished</b>     | <b>UV Satin Lacquered</b>  |

|   |   |
|---|---|
| <b>Structure</b>                        | <b>Solid</b>  |
| <b>Veneer Thickness (if applicable)</b> | <b>-</b>  |
| <b>Length Spec (including average)</b>  | <b>400-1200 Ave 700</b>   |
| <b>Width Tolerance</b>                  | <b>+/- 0.2mm</b>  |
| <b>Type of Finish</b>                   | <b>Gold Stained &amp; UV Satin lacquered.<br/>Handscraped textured finish</b> |
| <b>Gloss Level</b>                      | <b>30% +/-5%</b>  |
| <b>Live Knot &amp; Filler Colour</b>    | <b>Up to 30mm in size, Dark Brown Filler</b>                                  |
| <b>Dead Knot</b>                        | <b>&lt;30mm filled</b>  |
| <b>Colour Difference</b>                | <b>Colour difference between boards allowed</b>                               |
| <b>Sapwood</b>                          | <b>-</b>  |
| <b>Grain</b>                            | <b>All grains patterns acceptable</b>   |
| <b>Split</b>                            | <b>Splits acceptable up to any size</b>                                       |
| <b>Formaldehyde</b>                     | <b>E1</b>   |
| <b>Bowing</b>                           | <b>&lt;0.5% of the length</b>   |
| <b>Moisture Content</b>                 | <b>8-10%</b>  |
| <b>Installation Method</b>              | <b>Secret Nailed or stuck down</b>  |
| <b>Suitable to use with UHF</b>         | <b>Yes, see guide</b>   |



YOUR VISION

OUR CREATION

### Solid Wood Technical Information



|                     |   |
|---------------------|---|
| <b>Product</b>      | <b>Caledonian Eng Oak<br/>Rustic Brush UV Oiled<br/>148mm 14/3mm 1860mm</b> |
| <b>Number</b>       | <b>524004</b>   |
| <b>Construction</b> | <b>Engineered 3 layer</b>   |
| <b>Size</b>         | <b>148mm x 14mm x 1860mm</b>  |
| <b>Finished</b>     | <b>UV Oiled</b>   |

|   |   |
|---|---|
| <b>Structure</b>                        | <b>Engineered 3 layer</b>                       |
| <b>Veneer Thickness (if applicable)</b> | <b>3mm +/-0.30mm</b>                            |
| <b>Length Spec (including average)</b>  | <b>Fixed 1860 some half boards</b>              |
| <b>Width Tolerance</b>                  | <b>+/- 0.2mm</b>                                |
| <b>Type of Finish</b>                   | <b>Brushed &amp; UV oiled</b>                   |
| <b>Gloss Level</b>                      | <b>10% +/-5%</b>                                |
| <b>Live Knot &amp; Filler Colour</b>    | <b>Healthy, not limited Dark Brown Filler</b>   |
| <b>Dead Knot</b>                        | <b>&lt;30mm filled</b>                          |
| <b>Colour Difference</b>                | <b>Colour difference between boards allowed</b> |
| <b>Sapwood</b>                          | <b>U0 to 15% allowed</b>                        |
| <b>Grain</b>                            | <b>All grains patterns acceptable</b>           |
| <b>Split</b>                            | <b>Hairline split up to 10mm acceptable</b>     |
| <b>Formaldehyde</b>                     | <b>E1</b>                                       |
| <b>Bowing</b>                           | <b>&lt;0.5% of the length</b>                   |
| <b>Moisture Content</b>                 | <b>8-10%</b>                                    |
| <b>Installation Method</b>              | <b>Floated or stuck down</b>                    |
| <b>Suitable to use with UHF</b>         | <b>Yes, see guide</b>                           |



YOUR VISION

OUR CREATION

### Solid Wood Technical Information



|                     |   |
|---------------------|---|
| <b>Product</b>      | <b>Caledonian Eng Oak<br/>Rustic UV Oiled 148mm<br/>14/3mm 1860mm</b> |
| <b>Number</b>       | <b>524006</b>   |
| <b>Construction</b> | <b>Engineered 3 layer</b>   |
| <b>Size</b>         | <b>148mm x 14mm x 1860mm</b>  |
| <b>Finished</b>     | <b>UV Oiled</b>   |

|   |   |
|---|---|
| <b>Structure</b>                        | <b>Engineered 3 layer</b>                       |
| <b>Veneer Thickness (if applicable)</b> | <b>3mm +/-0.30mm</b>                            |
| <b>Length Spec (including average)</b>  | <b>Fixed 1860 some half boards</b>              |
| <b>Width Tolerance</b>                  | <b>+/- 0.2mm</b>                                |
| <b>Type of Finish</b>                   | <b>UV oiled</b>                                 |
| <b>Gloss Level</b>                      | <b>10% +/-5%</b>                                |
| <b>Live Knot &amp; Filler Colour</b>    | <b>Healthy, not limited Dark Brown Filler</b>   |
| <b>Dead Knot</b>                        | <b>&lt;30mm filled</b>                          |
| <b>Colour Difference</b>                | <b>Colour difference between boards allowed</b> |
| <b>Sapwood</b>                          | <b>U0 to 15% allowed</b>                        |
| <b>Grain</b>                            | <b>All grains patterns acceptable</b>           |
| <b>Split</b>                            | <b>Hairline spilt up to 10mm acceptable</b>     |
| <b>Formaldehyde</b>                     | <b>E1</b>                                       |
| <b>Bowing</b>                           | <b>&lt;0.5% of the length</b>                   |
| <b>Moisture Content</b>                 | <b>8-10%</b>                                    |
| <b>Installation Method</b>              | <b>Floated or stuck down</b>                    |
| <b>Suitable to use with UHF</b>         | <b>Yes, see guide</b>                           |



YOUR VISION

OUR CREATION

### Solid Wood Technical Information



|                     |  |
|---------------------|--|
| <b>Product</b>      | <b>Contemporary Eng Oak<br/>Rustic Knotty Brush White<br/>Washed 190mm 15/4mm<br/>1900mm</b> |
| <b>Number</b>       | <b>527011A</b>   |
| <b>Construction</b> | <b>Engineered 3 layer</b>  |
| <b>Size</b>         | <b>190mm x 15mm x 1900mm</b>   |
| <b>Finished</b>     | <b>UV Oiled</b>  |

|   |   |
|---|---|
| <b>Structure</b>                        | <b>Engineered 3 layer</b>                       |
| <b>Veneer Thickness (if applicable)</b> | <b>4mm +/-0.30mm</b>                            |
| <b>Length Spec (including average)</b>  | <b>Fixed 1900 some half boards</b>              |
| <b>Width Tolerance</b>                  | <b>+/- 0.2mm</b>                                |
| <b>Type of Finish</b>                   | <b>White washed &amp; UV oiled</b>              |
| <b>Gloss Level</b>                      | <b>10% +/-5%</b>                                |
| <b>Live Knot &amp; Filler Colour</b>    | <b>Healthy, not limited Dark Brown Filler</b>   |
| <b>Dead Knot</b>                        | <b>&lt;35mm filled</b>                          |
| <b>Colour Difference</b>                | <b>Colour difference between boards allowed</b> |
| <b>Sapwood</b>                          | <b>Acceptable on edge</b>                       |
| <b>Grain</b>                            | <b>All grains patterns acceptable</b>           |
| <b>Split</b>                            | <b>Acceptable to width of 4mm x 100mm</b>       |
| <b>Formaldehyde</b>                     | <b>E1</b>                                       |
| <b>Bowing</b>                           | <b>&lt;0.5% of the length</b>                   |
| <b>Moisture Content</b>                 | <b>8-10%</b>                                    |
| <b>Installation Method</b>              | <b>Floated or stuck down</b>                    |
| <b>Suitable to use with UHF</b>         | <b>Yes, see guide</b>                           |



YOUR VISION

OUR CREATION

### Solid Wood Technical Information



|                     |   |
|---------------------|---|
| <b>Product</b>      | Contemporary Eng Oak<br>White Grey Rustic Stain<br>Brush Matt Lacq 180mm<br>14/2.5mm 2200mm |
| <b>Number</b>       | 527046  |
| <b>Construction</b> | Engineered 3 layer  |
| <b>Size</b>         | 180mm x 14mm x 2200mm   |
| <b>Finished</b>     | UV Matt Lacquered   |

|   |  |
|---|--|
| <b>Structure</b>                        | Engineered 3 layer                       |
| <b>Veneer Thickness (if applicable)</b> | 2.5mm +/-0.30mm                          |
| <b>Length Spec (including average)</b>  | Fixed 2200 some half boards              |
| <b>Width Tolerance</b>                  | +/- 0.2mm                                |
| <b>Type of Finish</b>                   | Cream Stained, Brushed & Matt Lacquered  |
| <b>Gloss Level</b>                      | 10% +/-5%                                |
| <b>Live Knot &amp; Filler Colour</b>    | Healthy, <35mm Dark Brown Filler         |
| <b>Dead Knot</b>                        | <25mm filled                             |
| <b>Colour Difference</b>                | Colour difference between boards allowed |
| <b>Sapwood</b>                          | Acceptable on edge                       |
| <b>Grain</b>                            | All grains patterns acceptable           |
| <b>Split</b>                            | Acceptable to width of 4mm x 100mm       |
| <b>Formaldehyde</b>                     | E1                                       |
| <b>Bowing</b>                           | <0.5% of the length                      |
| <b>Moisture Content</b>                 | 8-10%                                    |
| <b>Installation Method</b>              | Floated or stuck down                    |
| <b>Suitable to use with UHF</b>         | Yes, see guide                           |